

ATTY. DOCKET NO. WEST14-00029

PATENT

APPARATUS FOR REALLOCATING COMMUNICATION RESOURCES TO ESTABLISH A  
PRIORITY CALL IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM

Inventor(s):

Paul F. Struhsaker  
5304 Brouette Court  
Plano  
Collin County  
Texas 75023  
United States Citizen

Assignee:

Raze Technologies, Inc.  
2540 East Plano Parkway  
Suite 188  
Plano, Texas 75074-7460

CERTIFICATE OF EXPRESS MAIL	
I hereby certify that this correspondence, including the attachments listed, is being mailed in an envelope addressed to Commissioner of Patents and Trademarks, Washington, DC 20231, using the Express Mail Post Office to Addressee service of the United States Postal Service on the date shown below.	
<i>Laura Zarate</i> Printed Name of Person Mailing	EL749593453us Express Mail Receipt No.
<i>Laura Zarate</i> Signature of Person Mailing	4-20-01 Date

William A. Munck  
John T. Mockler  
Novakov Davis & Munck, P.C.  
Three Galleria Tower  
13155 Noel Road, Suite 900  
Dallas, Texas 75240  
(214) 922-9221

APPARATUS FOR REALLOCATING COMMUNICATION RESOURCES TO ESTABLISH A  
PRIORITY CALL IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM

## CROSS-REFERENCE TO RELATED APPLICATIONS

5

The present invention is related to those disclosed in the following United States Provisional and Non-Provisional Patent Applications:

1. Serial No. 09/713,684, filed on November 15, 2000, entitled "SUBSCRIBER INTEGRATED ACCESS DEVICE FOR USE IN WIRELESS AND WIRELINE ACCESS SYSTEMS";
2. [Docket No. WEST14-00005] filed concurrently herewith, entitled "WIRELESS COMMUNICATION SYSTEM USING BLOCK FILTERING AND FAST EQUALIZATION-DEMODULATION AND METHOD OF OPERATION";
- 15 3. [Docket No. WEST14-00014], filed concurrently herewith, entitled "APPARATUS AND ASSOCIATED METHOD FOR OPERATING UPON DATA SIGNALS RECEIVED AT A RECEIVING STATION OF A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM";
- 20 4. [Docket No. WEST14-00015], filed concurrently herewith, entitled "APPARATUS AND METHOD FOR OPERATING A SUBSCRIBER INTERFACE IN A FIXED WIRELESS SYSTEM";

5. [Docket No. WEST14-00016], filed concurrently herewith,  
entitled "APPARATUS AND METHOD FOR CREATING SIGNAL AND  
PROFILES AT A RECEIVING STATION";
6. [Docket No. WEST14-00017], filed concurrently herewith,  
entitled "SYSTEM AND METHOD FOR INTERFACE BETWEEN A SUBSCRIBER  
MODEM AND SUBSCRIBER PREMISES INTERFACES";
7. [Docket No. WEST14-00018], filed concurrently herewith,  
entitled "BACKPLANE ARCHITECTURE FOR USE IN WIRELESS AND  
WIRELINE ACCESS SYSTEMS";
8. [Docket No. WEST14-00019], filed concurrently herewith,  
entitled "SYSTEM AND METHOD FOR ON-LINE INSERTION OF LINE  
REPLACEABLE UNITS IN WIRELESS AND WIRELINE ACCESS SYSTEMS" ;
9. [Docket No. WEST14-00020], filed concurrently herewith,  
entitled "SYSTEM FOR COORDINATION OF TDD TRANSMISSION BURSTS  
WITHIN AND BETWEEN CELLS IN A WIRELESS ACCESS SYSTEM AND  
METHOD OF OPERATION";
10. [Docket No. WEST14-00021], filed concurrently herewith,  
entitled "REDUNDANT TELECOMMUNICATION SYSTEM USING MEMORY  
EQUALIZATION APPARATUS AND METHOD OF OPERATION";
11. [Docket No. WEST14-00022], filed concurrently herewith,  
entitled "WIRELESS ACCESS SYSTEM FOR ALLOCATING AND

SYNCHRONIZING UPLINK AND DOWNLINK OF TDD FRAMES AND METHOD OF OPERATION";

12. [Docket No. WEST14-00023], filed concurrently herewith, entitled "TDD FDD AIR INTERFACE";

5 13. [Docket No. WEST14-00024], filed concurrently herewith, entitled "APPARATUS, AND AN ASSOCIATED METHOD, FOR PROVIDING WLAN SERVICE IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM";

14. [Docket No. WEST14-00026], filed concurrently herewith, entitled "WIRELESS ACCESS SYSTEM USING MULTIPLE MODULATION";

15. [Docket No. WEST14-00027], filed concurrently herewith, entitled "WIRELESS ACCESS SYSTEM AND ASSOCIATED METHOD USING MULTIPLE MODULATION FORMATS IN TDD FRAMES ACCORDING TO SUBSCRIBER SERVICE TYPE";

16. [Docket No. WEST14-00028], filed concurrently herewith, entitled "APPARATUS FOR ESTABLISHING A PRIORITY CALL IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM";

17. [Docket No. WEST14-00030], filed concurrently herewith, entitled "METHOD FOR ESTABLISHING A PRIORITY CALL IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM";

20 18. [Docket No. WEST14-00033], filed concurrently herewith, entitled "SYSTEM AND METHOD FOR PROVIDING AN IMPROVED COMMON

CONTROL BUS FOR USE IN ON-LINE INSERTION OF LINE REPLACEABLE  
UNITS IN WIRELESS AND WIRELINE ACCESS SYSTEMS";

19. Serial No. 60/262,712, filed on January 19, 2001, entitled  
"WIRELESS COMMUNICATION SYSTEM USING BLOCK FILTERING AND FAST  
EQUALIZATION-DEMODULATION AND METHOD OF OPERATION" [Docket No.  
WEST14-00005];

20. Serial No. 60/262,825, filed on January 19, 2001, entitled  
"APPARATUS AND ASSOCIATED METHOD FOR OPERATING UPON DATA  
SIGNALS RECEIVED AT A RECEIVING STATION OF A FIXED WIRELESS  
ACCESS COMMUNICATION SYSTEM" [Docket No. WEST14-00014];

21. Serial No. 60/262,698, filed on January 19, 2001, entitled  
"APPARATUS AND METHOD FOR OPERATING A SUBSCRIBER INTERFACE IN  
A FIXED WIRELESS SYSTEM" [Docket No. WEST14-00015];

22. Serial No. 60/262,827, filed on January 19, 2001, entitled  
"APPARATUS AND METHOD FOR CREATING SIGNAL AND PROFILES AT A  
RECEIVING STATION" [Docket No. WEST14-00016];

23. Serial No. 60/262,826, filed on January 19, 2001, entitled  
"SYSTEM AND METHOD FOR INTERFACE BETWEEN A SUBSCRIBER MODEM  
AND SUBSCRIBER PREMISES INTERFACES" [Docket No. WEST14-00017];

24. Serial No. 60/262,951, filed on January 19, 2001, entitled  
"BACKPLANE ARCHITECTURE FOR USE IN WIRELESS AND WIRELINE  
ACCESS SYSTEMS" [Docket No. WEST14-00018];

25. Serial No. 60/262,824, filed on January 19, 2001, entitled "SYSTEM AND METHOD FOR ON-LINE INSERTION OF LINE REPLACEABLE UNITS IN WIRELESS AND WIRELINE ACCESS SYSTEMS" [Docket No. WEST14-00019];

5 26. Serial No. 60/263,101, filed on January 19, 2001, entitled "SYSTEM FOR COORDINATION OF TDD TRANSMISSION BURSTS WITHIN AND BETWEEN CELLS IN A WIRELESS ACCESS SYSTEM AND METHOD OF OPERATION" [Docket No. WEST14-00020];

27. Serial No. 60/263,097, filed on January 19, 2001, entitled "REDUNDANT TELECOMMUNICATION SYSTEM USING MEMORY EQUALIZATION APPARATUS AND METHOD OF OPERATION" [Docket No. WEST14-00021];

28. Serial No. 60/273,579, filed March 5, 2001, entitled "WIRELESS ACCESS SYSTEM FOR ALLOCATING AND SYNCHRONIZING UPLINK AND DOWNLINK OF TDD FRAMES AND METHOD OF OPERATION" [Docket No. WEST14-00022];

29. Serial No. 60/262,955, filed January 19, 2001, entitled "TDD FDD AIR INTERFACE" [Docket No. WEST14-00023];

30. Serial No. 60/262,708, filed on January 19, 2001, entitled "APPARATUS, AND AN ASSOCIATED METHOD, FOR PROVIDING WLAN SERVICE IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM" [Docket No. WEST14-00024];

31. Serial No. 60/273,689, filed March 5, 2001, entitled "WIRELESS ACCESS SYSTEM USING MULTIPLE MODULATION" [Docket No. WEST14-00026];
32. Serial No. 60/273,757, filed March 5, 2001, entitled "WIRELESS ACCESS SYSTEM AND ASSOCIATED METHOD USING MULTIPLE MODULATION FORMATS IN TDD FRAMES ACCORDING TO SUBSCRIBER SERVICE TYPE" [Docket No. WEST14-00027];
33. Serial No. 60/270,378, filed February 21, 2001, entitled "APPARATUS FOR ESTABLISHING A PRIORITY CALL IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM" [Docket No. WEST14-00028]; and
34. Serial No. 60/270,430, filed February 21, 2001, entitled "METHOD FOR ESTABLISHING A PRIORITY CALL IN A FIXED WIRELESS ACCESS COMMUNICATION SYSTEM" [Docket No. WEST14-00030].

The above applications are commonly assigned to the assignee of the present invention. The disclosures of these related patent applications are hereby incorporated by reference for all purposes as if fully set forth herein. The present application hereby claims the benefit under Title 35, United States Code, §119(e) of the above provisional and non-provisional United States Patent Applications.

**TECHNICAL FIELD OF THE INVENTION**

The present invention relates generally to a manner by which to initiate establishment of a priority call, such as a call to request emergency assistance in a FWA (fixed wireless access), or other, communication system. More particularly, the present invention relates to apparatus, and an associated method, by which to effectuate the priority call even when communication resources are not initially available to establish the call. The initial unavailability of the communication resources is not made known to the user initiating the call as normal system operation is emulated at a subscriber station from which the call originates. And, when the call is determined to be a priority call, the communication resources of the communication system are reallocated to provide communication resources to permit the establishment of the priority call.

**BACKGROUND OF THE INVENTION**

Telecommunications access systems provide for voice, data, and multimedia transport and control between the central office (CO) of the telecommunications service provider and the subscriber (customer) premises. Prior to the mid-1970s, the subscriber was provided phone lines (e.g., voice frequency (VF) pairs) directly



from the Class 5 switching equipment located in the central office of the telephone company. In the late 1970s, digital loop carrier (DLC) equipment was added to the telecommunications access architecture. The DLC equipment provided an analog phone  
5 interface, voice CODEC, digital data multiplexing, transmission interface, and control and alarm remotely from the central office to cabinets located within business and residential locations for approximately 100 to 2000 phone line interfaces. This distributed access architecture greatly reduced line lengths to the subscriber and resulted in significant savings in both wire installation and maintenance. The reduced line lengths also improved communication performance on the line provided to the subscriber.

By the late 1980s, the limitations of data modem connections over voice frequency (VF) pairs were becoming obvious to both  
15 subscribers and telecommunications service providers. ISDN (Integrated Services Digital Network) was introduced to provide universal 128 kbps service in the access network. The subscriber interface is based on 64 kbps digitization of the VF pair for digital multiplexing into high speed digital transmission streams  
20 (e.g., T1/T3 lines in North America, E1/E3 lines in Europe). ISDN was a logical extension of the digital network that had evolved throughout the 1980s. The rollout of ISDN in Europe was highly

successful. However, the rollout in the United States was not successful, due in part to artificially high tariff costs which greatly inhibited the acceptance of ISDN.

More recently, the explosion of the Internet and deregulation  
5 of the telecommunications industry have brought about a broadband  
revolution characterized by greatly increased demands for both  
voice and data services and greatly reduced costs due to  
technological innovation and intense competition in the  
telecommunications marketplace. To meet these demands, high speed  
10 DSL (digital subscriber line) modems and cable modems have been  
developed and introduced. The DLC architecture was extended to  
provide remote distributed deployment at the neighborhood cabinet  
level using DSL access multiplexer (DSLAM) equipment. The  
increased data rates provided to the subscriber resulted in upgrade  
15 DLC/DSLAM transmission interfaces from T1/E1 interfaces (1.5/2.0  
Mbps) to high speed DS3 and OC3 interfaces. In a similar fashion,  
the entire telecommunications network backbone has undergone and is  
undergoing continuous upgrade to wideband optical transmission and  
switching equipment.

20 Similarly, wireless access systems have been developed and  
deployed to provide broadband access to both commercial and  
residential subscriber premises. Initially, the market for

wireless access systems was driven by rural radiotelephony deployed solely to meet the universal service requirements imposed by government (i.e., the local telephone company is required to serve all subscribers regardless of the cost to install service). The  
5 cost of providing a wired connection to a small percentage of rural subscribers was high enough to justify the development and expense of small-capacity wireless local loop (WLL) systems.

Deregulation of the local telephone market in the United States (e.g., Telecommunications Act of 1996) and in other countries shifted the focus of fixed wireless access (FWA) systems deployment from rural access to competitive local access in more urbanized areas. In addition, the age and inaccessibility of much of the older wired telephone infrastructure makes FWA systems a cost-effective alternative to installing new, wired infrastructure.

Also, it is more economically feasible to install FWA systems in  
15 developing countries where the market penetration is limited (i.e., the number and density of users who can afford to pay for services is limited to small percent of the population) and the rollout of wired infrastructure cannot be performed profitably. In either  
20 case, broad acceptance of FWA systems requires that the voice and data quality of FWA systems must meet or exceed the performance of wired infrastructure.

Wireless access systems must address a number of unique operational and technical issues including:

1) Relatively high bit error rates (BER) compared to wire line or optical systems; and

2) Transparent operation with network protocols and protocol time constraints for the following protocols:

a) ATM;

b) Class 5 switch interfaces (domestic GR-303 and international V5.2);

c) TCP/IP with quality-of-service QoS for voice over IP (VoIP) (i.e., RTP) and other H.323 media services;

d) Distribution of synchronization of network time out to the subscribers;

3) Increased use of voice, video and/or media compression and concentration of active traffic over the air interface to conserve bandwidth;

4) Switching and routing within the access system to distribute signals from the central office to multiple remote cell sites containing multiple cell sectors and one or more frequencies of operation per sector; and

5) Remote support and debugging of the subscriber equipment,

including remote software upgrade and provisioning.

Unlike physical optical or wire systems that operate at bit error rates (BER) of  $10^{-11}$ , wireless access systems have time varying channels that typically provide bit error rates of  $10^{-3}$  to  $10^{-6}$ . The wireless physical (PHY) layer interface and the media access control (MAC) layer interface must provide modulation, error correction and ARQ protocol that can detect and, where required, correct or retransmit corrupted data so that the interfaces at the network and at the subscriber site operate at wire line bit error rates.

The wide range of equipment and technology capable of providing either wireline (i.e., cable, DSL, optical) broadband access or wireless broadband access has allowed service providers to match the needs of a subscriber with a suitable broadband access solution. However, in many areas, the cost of cable modem or DSL service is high. Additionally, data rates may be slow or coverage incomplete due to line lengths. In these areas and in areas where the high cost of replacing old telephone equipment or the low density of subscribers makes it economically unfeasible to introduce either DSL or cable modem broadband access, fixed wireless broadband systems offer a viable alternative. Fixed wireless broadband systems use a group of transceiver base stations

to cover a region in the same manner as the base stations of a cellular phone system. The base stations of a fixed wireless broadband system transmit forward channel (i.e., downstream) signals in directed beams to fixed location antennas attached to the residences or offices of subscribers. The base stations also receive reverse channel (i.e., upstream) signals transmitted by the broadband access equipment of the subscriber.

Unfortunately, the diversity of broadband access technology has resulted in a lack of standardization in the broadband access equipment. Cable modems and DSL routers are incompatible with each other and with fiber optic equipment. Different service providers locate broadband access equipment in different locations on the subscriber premises. Often this equipment is located inside the office or residence of the subscriber, which makes it inaccessible to maintenance workers unless the subscriber is present to admit the workers to the premises. The lack of standardization of broadband access equipment and the frequent inaccessibility of such equipment adds to the cost and complexity of broadband access.

Therefore, there is a need in the art for broadband access equipment that can be readily and inexpensively deployed in the large domestic and international markets that are not currently served by wired or wireless broadband access technology. Further,

there is a need for an apparatus to increase the communication capacity of the communication system.

Concentration techniques are utilized in construction of many multi-user communication systems. Concentration techniques, generally, refer to selection of the number of users permitted to be part of the system to be greater, by some factor, than the actual capacity of the communication system. Statistical, or other, analysis is made of the likely number of users of the communication system at any particular time, and the system is constructed to support a number of users based upon the expected number of users.

During times in which actual usage of the communication exceeds the capacity of the system, additional users, beyond the system's capacity, are prevented, or blocked, from access to the system.

When the communication system comprises a conventional wireline, telephonic communication system, the additional users are provided indication of their failure to access the system by alerting such users with audible alerts. The audible alerts are audibly distinct from normal dial tones generated during normal telephonic operation.

In a fixed wireless access communication system, capacity

limitations are possible between both the network infrastructure of the system and a correspondent node forming a terminating or originating station as well as, additionally, the radio links extending between the network infrastructure and the subscriber stations.

When, for instance, a user at the subscriber station needs to place a priority call, such as a request for emergency assistance to an emergency dispatch center, access to the communication system to communicate with the emergency dispatch center is essential. A need therefore exists to provide access to a communication system to establish the priority call with the emergency dispatch center. It would also be desirable to provide a manner by which to operate the communication system in which the user is not made aware of an initial blockage from access to the system if access shall subsequently be granted.

It is in light of this background information related to radio communication systems that the significant improvements of the present invention have evolved.



## SUMMARY OF THE INVENTION

The present invention, accordingly, advantageously provides apparatus, and an associated method, by which to initiate establishment of a priority call, such as a call to request emergency assistance, in a FWA (fixed wireless access), or other, communication system.

Through operation of an embodiment of the present invention, a manner is provided by which to effectuate the priority call even when the communication resources are not initially available to establish the call.

When a call is initiated, the initial unavailability of the communication resources is not made known to the user initiating the call as normal system operation is emulated at the subscriber station at which the call is originated. The communication resources of the communication system are reallocated, when the call is determined to be a priority call, to provide communication resources to permit the establishment of the priority call.

In one aspect of the present invention, apparatus is provided for a subscriber station operable in a fixed wireless access communication system. When a priority call is originated at the subscriber station, the user of the subscriber station takes the telephonic station located thereat off-hook. When the telephonic

station is off-hook, a call establishment message is generated and sent by way of a radio link to network infrastructure of the fixed wireless access system. The establishment message is generated as a precursor to a request to establish the call between the subscriber station and another communication station. Detection is made at the network infrastructure of the call establishment message. Responsive thereto, determination is made of the communication resource availability in the communication system to establish an additional call, of indeterminate priority. A response indicating whether communication resources are available in the communication system to establish the call of indeterminate priority is returned to the subscriber station.

A response detector at the subscriber station is coupled to receive indications of the response to the call establishment message. Indication of whether communication resources are available to establish the call is detected thereat. If communication resources are unavailable, a call set-up emulator is operable to emulate at the subscriber station normal call set-up operations. To the user of the subscriber station at which the call is initiated, call set-up operations appear to be normally progressing.

Dialing digits associated with the terminating station with

which the call is to be established are entered at the subscriber station. A dialing digit signal is then sent to the network infrastructure. Determination is made at the network infrastructure of the priority to be associated with the call which is to be established. If the call is a priority call, such as a call to an emergency dispatch center, e.g., indicated by a pseudo-universal dialing code, such as 9-1-1, resource reallocations are effectuated to permit the establishment of the call. Thereafter, the call is established.

In one implementation, apparatus is provided for a subscriber station operable in the FWA system. A call set-up emulator is selectably operable to emulate normal call set-up operations at the subscriber station even when communication resources are not initially available to establish a call by the subscriber station. A dial-tone generator generates a dial tone audibly detectable by the user of the subscriber station in which the call is originated. Dialing digits associated with the call originated at the subscriber station are also enterable in apparent normal fashion at the subscriber station. Upon subsequent reallocation of communication resources in the FWA communication system, the call establishment commences in normal manner.

In a further implementation, apparatus is provided for the

network infrastructure of the FWA system, such as at an access processor or base transceiver station of the system. A detector is coupled to detect a call establishment message transmitted to the network infrastructure. Responsive to receipt of the call establishment message, determinations are made of the availability of communication resources to establish a call in the communication system. A response is then sent to the originating subscriber station. Thereafter, indications of the identity of the terminating station to which a call is to be established are received at the network infrastructure. If the identify of the terminating station indicates that the call is a priority call, reallocation of communication resources is made, if necessary, to permit the establishment of the call. If communication resources are not otherwise available, an ongoing communication session is terminated to provide the communication resources to effectuate the call.

In these and another aspects, therefore, apparatus, and an associated method, is provided for a multi-user FWA (fixed wireless access) communication system in which a plurality of subscriber stations are operable to communicate by way of radio links with network infrastructure to which an emergency dispatch center is coupled. A call request originated by a selected subscriber

station is sent to the network infrastructure to request establishment of a call between the selected subscriber station and the emergency dispatch center. A communication resource availability determiner is operable responsive to receipt at the  
5 network infrastructure of the call request to determine whether communication resources are available to establish the call between the selected subscriber station and the emergency dispatch center.

A resource reallocator is coupled to the communication resource availability determiner. The resource reallocator is selectably operable to reallocate communication resources in the FWA communication system to permit establishment of the call between the selected subscriber station and the emergency dispatch center.

The present invention will be better understood when read in light of the accompanying drawings which are described in the detailed description hereinbelow and in light of the claims  
15 appended hereto.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a functional block diagram of an exemplary fixed wireless access (FWA) network in which an embodiment of the present invention is operable.

5 Figure 2 illustrates an exemplary data frame, as defined by the fixed wireless access network in Figure 1, according to an embodiment of the present invention;

Figure 3 illustrates a functional block diagram of portions of the fixed wireless access communication system shown in Figure 1.

Figure 4 illustrates a message sequence diagram exemplary of signaling generated during operation of the communication system shown in Figures 1 and 3 pursuant to an embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Referring first to Figure 1, a communication system, shown generally at 10, provides for communications with the subscriber stations, of which the subscriber station 12 is exemplary. Communications are effectuated with the subscriber station by way of radio links formed upon an air interface 14. Data originated at an appropriately-positioned subscriber station can be communicated to a correspondent node, 16 by way of a communication path by way of the radio links formed upon the air interface. Data originated at the correspondent node 16 can be communicated upon a communication path formed between a correspondent node and a subscriber station. Two-way communication between the subscriber station and the correspondent node is thereby possible.

In the exemplary implementation, the communication system 10 forms a fixed wireless access (FWA) system coupled to a network backbone, of which the combined path data network (PDN) and public-switched telephonic network (PSTN) 18 is representative in the figure.

While the following description of operation of an embodiment of the present invention shall describe its operation with respect to the exemplary implementation of the communication system shown in the figure, it should be understood that operation of an

embodiment of the present invention is analogously also operable in other types of communication systems which use concentration techniques or otherwise are susceptible to access limitations.

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2



permitted to be associated with a particular base transceiver station. Not all of the subscriber stations are likely to attempt to effectuate simultaneous communication sessions, thereby permitting the number of permitted subscriber stations to be  
5 increased.

While any of the a large variety of different types of communications are effectuable, of significance to an embodiment of the present invention are telephonic communications originated at the subscriber station. A telephonic station 26 is here shown to be located at the subscriber station 12.

Use of the terminology communications by the subscriber station and by the telephonic station shall be used, at times, interchangeably below to indicate communications by the telephonic station with the correspondent node 16. And, while only a telephonic station 26 is shown to be positioned at the subscriber station, other types of communication devices such as computer stations and consumer-electronic devices, can also be represented at the subscriber station.

An integrated access device (IAD) 28 is also shown to be  
20 positioned at the subscriber station. The integrated access device (IAD) unit includes transceiver circuitry capable of communicating by way of the air interface with the base transceiver station 22.

The telephonic station 26 is coupled to the integrated access device 28 and communications are effectuated with the subscriber station by way of the integrated access device.

5 The base transceiver station 22 forms a portion of the network infrastructure of the fixed wireless access system. Groups of base transceiver stations are coupled to an access processor (AP) 32. And, in turn, the access process is coupled to the network 18. During operation of an embodiment of the present invention, communication resources required to establish a call between the telephonic station 26 and the correspondent node 16 are selectably provided. Communication resources both at the air interface 14 and through the network 18 must be available to establish the call between the telephonic station 26 and the correspondent node 16.

15 Figure 2 illustrates portions of the communication system 10 to illustrate operation of an embodiment of the present invention.

Operation of an embodiment of the present invention permits a user of the telephonic station 26 positioned at the subscriber station 12 to originate a call to an emergency dispatch center 34 at which the correspondent node 16 is located.

20 Elements shown in the figure are functional representations, portions of which are implemented, in exemplary implementation, as algorithms executable at processing devices. Additionally,

functional operation of the various elements, or portions thereof, can be distributed at several locations or elements of the communication system. Here, for instance, the transmit and receive circuitry portions 36 and 38 are implemented at the integrated  
5 access device 28, at the telephonic station 26, or at other portions of the subscriber stations.

When a call is placed to the emergency dispatch center, a pseudo-universal dialing code, such as a 9-1-1 dialing code is entered at the telephonic station of the subscriber station.

A user interface 42 is also positioned at the subscriber station. The user interface includes, for instance, an actuation key pad located on the telephonic station which permits user actuation thereof to enter dialing digits associated with a terminating station such as the correspondent node 16 at the emergency dispatch center 34. The user interface is also representative of a hook switch associated with the telephonic station upon which a telephonic handset is conventionally positioned, to be removed therefrom when a call is to be initiated.

The user interface is coupled to apparatus 44 of an embodiment  
20 of the present invention. The apparatus 44 is formed of functional elements implemented, for instance, by algorithms executable by control circuitry.

Here, a call establishment message generator 46 is coupled to the user interface to receive indications of off-hook indications indicated thereat. An off-hook indication is indicated when a telephonic station is taken off the hook switch when a user intends  
5 to initiate a call with a terminating station. The call establishment message generator generates a call establishment message when the off-hook indication is provided thereto. The call establishment message is provided to the transmit circuitry 36 to be transmitted to the network infrastructure to inform the network infrastructure of the imminent request for establishment of a call with a terminating station.

The network infrastructure, here formed of both the base transceiver station 22 and access processor 32 is also shown to include both transmit circuitry and receive circuitry portions 52 and 54, respectively. The transmit and receive circuitry portions are implemented, for example, at the base transceiver station 22.

The call establishment message transmitted by the subscriber station to the network infrastructure is detected at the receive circuitry 52. Apparatus of an embodiment of the present invention,  
20 here referenced at 56 is coupled to the receive and transmit circuitry 52 and 54. Elements forming the apparatus 56 are also functionally represented and can be implemented in any of various

manners, including by algorithms executable by control circuitry. And, the elements forming the apparatus 56 can be distributed at different locations of the network infrastructure or coupled thereto.

5       When a call establishment message is received at the receive circuitry, detection is made of its reception by a call establishment message detector 58. The call establishment message detector is coupled to a communication resource availability determiner 62. The communication resource availability determiner is operable at least responsive to detection of reception of the call establishment message at the network infrastructure. The communication resource availability determiner is operable to determine the availability of communication resources, both in the network 18 and upon the air interface 14, of communication resources to establish a call of indeterminate priority. Determinations are made, for instance, responsive to indications of other ongoing communication sessions with other subscriber stations as well as ongoing communication sessions making use of the network 18.

20       Determinations made by the determiner 62 are provided to a response generator 64. The response generator generates a response signal which is provide to the transmit circuitry 54. The response

signal is transmitted by way of the air interface 14 to the subscriber station 12. The response serves to acknowledge reception at the network infrastructure of the call establishment message and also to provide an indication to the subscriber station  
5 of the availability of communication resources to establish a call originated at the subscriber station.

When the response is received at the receive circuitry 38 of the subscriber station, a response detector 68 detects reception at the subscriber station of the response. If the response indicates that communication resources are unavailable to establish a call, originated at the subscriber station, an indication is provided to a call set-up emulator 72. The call set-up emulator is operable to emulate normal operation of call set-up procedures even though the response indicates the communication resources to be unavailable to establish the call. The call set-up emulator includes, for instance, a dial tone generator which generates a conventional telephonic dial tone audibly detectable by a user of the telephonic station. Here, the oscillator 74 is representative of an oscillating signal used in the generation of a dial tone. The  
20 emulator is also coupled to the user interface 42 to receive indications of dialing digits or other actuator inputs input by way of the user interface. For instance when dialing digits are

entered, the generated dial tone is terminated and appropriate audibly-detectable tones are generated responsive to the entry of the dialing digits or other input actuations.

Indications of the entered dialing digits are also provided to  
5 a dialing digit signal generator 76. The dialing signal generator generates a dialing digit signal which is provided to the transmit circuitry 36 to be transmitted to the network infrastructure.

When the dialing digit signal is received at the receive circuitry, detection of the signal is made by a dialing digit indication detector 82. The detector 82 detects the values of the dialing digits. Detection is at least made as to whether the values of the dialing digits are those corresponding to the emergency dispatch center, or other priority location. When detection is made of dialing digits corresponding to the emergency dispatch center, or other priority location, an indication of such is given to a resource reallocator 84. The resource reallocator is operable to reallocate the allocation of communication resources in the communication system to permit the establishment of the call  
15  
20 Resource reallocation caused to be effectuated by the resource reallocator includes, for instance, termination of ongoing communication sessions to make available the communication

resources to permit the call to the emergency dispatch center, or other priority location, to be established. Selection of which of the ongoing communication session, or sessions, to be terminated is made, for instance, upon random selection, or based upon  
5 subscription service levels to which the different subscriber stations have subscribed.

Thereby, a call is able to be established between the subscriber station and the emergency dispatch center, even when the communication resources are not initially available to permit the establishment of the call. And, through the use of the call set-up emulator at the subscriber station, the originator of the call is not made aware of the initial unavailability of the communication resources.

Figure 3 again shows portions of the fixed wireless network, here shown at 300 of an embodiment of the present invention. The Fixed wireless network, is here show to include a subscriber integrated access device (SIAD) 304 located at a subscriber premises. The SIAD 304 includes radio circuitry 306 capable of transceiving radio signals. With a transceiver base station 308.

20 The radio circuitry 306 of the SIAD 304 is here capable of generating both voice and data packets, here represented by the blocks 312 and 314. The voice packets are representative of voice



packets generated during operation of a telephony handset which is operable in convention manner but connected to the radio circuitry of the SIAD.

The transceiver base station is coupled to an access processor  
5 shelf 322 which here functionally is shown to include a table 324 at which active call information is stored, and a resource allocator 326 which allocates communication resources in the fixed wireless network.

The access processor communicates traffic and signaling information by way of the element 328 on the lines 332 with a network interface 334.

The network interface 334 is coupled to the PSTN/IP network  
336.

The network 336 is, in tern, connected to a communication  
15 station, here located at an emergency dispatch center 338.

A telephony handset located at the SIAD 304 can be used, for instance, to phone an emergency request for emergency assistance to personnel at the emergency dispatch center. The call, when established, permits a call originator who places the call to  
20 request emergency assistance.

Due to the potentially emergency nature of the call, it is essential that the call be established. Due to the use of

concentration techniques in system construction, there is a possibility that system capacity would not permit establishment of the call, and the request for emergency assistance at the emergency dispatch center would not be completed.

5        During operation of an embodiment of the present invention, a manner is provided by which to better assure that the call is established.

10        Figure 4 illustrates a message sequence diagram, shown generally at 400, representative of operation of a fixed wireless network shown in Figure 3. Signaling is initiated at the SIAD 304 when a telephony handset is taken off-hook. As soon as the telephony handset is taken off-hook, a call establishment message is generated, indicated by the segment 404, and sent to the access processor 322. A determination is made as to whether resources are available to establish a call. In the exemplary scenario, resources are not available to establish a call, and an indication of the unavailability of the resources, indicated by the segment 15 406, is returned to the SIAD.

20        Upon receipt of the indication of the unavailability of the resources, normal call set-up procedures are emulated, indicated by the block 408. emulation procedures include, for instance, generation of a dial tone which is local to the SIAD but otherwise

appearing to be normal operation of the telephony handset to a user thereof. The user, upon detecting the dial tone, dials, or otherwise enters, digits associated with the emergency dispatch center, such as the emergency digits 9-1-1 forming a pseudo  
5 universal emergency number in the United States. The entered digits of the dialing code are captured, indicated at the block 410, and a digit message is generated and transmitted by the segment 412 to the access processor 322.

At the access processor a determination is made as to whether the values of the digits contain in the digit message are associated with the emergency dispatch center or are otherwise associated with the priority call. If not, a terminate call message indicated by the segment 414 is returned to the SIAD. A terminate call message is identified at the telephony handset at the SIAD as a fast busy signal.

If, conversely, the digit message is of values corresponding to an emergency dispatch center, or is otherwise representative of a priority call, a decision is made to permit the establishment of the call. To free resources to permit the establishment of the  
20 call, a nonpriority call is terminated, indicated by the block 416.

A non priority call is terminated, such as by randomly terminating an active call selected from the table 324, (shown in Figure 3). A

priority might also be associated with the act of calls, and a lowest-priority act of call is first-terminated. Or, a random termination of a lowest-priority call is performed. Thereby, resources are made available to establish the call between the telephony handset and the emergency dispatch center. Thereafter, and as indicated by the segment 418, a message is sent to the PSTN to cause a call to be established therethrough. Normal call operations, indicated by the block 422 is thereafter effectuated at the 911, or other priority call, continues until one side, or the other, of the communication sessions goes on-hook.

The previous descriptions are of preferred examples for implementing the invention, and the scope of the invention should not necessarily be limited by this description. The scope of the present invention is defined by the following claims.